





Hose break valves in female female manifold

Valvole di sicurezza (paracadute) in collettore femmina femmina



SPECIFICATIONS / SPECIFICHE	
Fluid viscosity / Viscosità fluido	ISO 3448
Filtration / Classe di contaminazione	ISO 4406
Fluid temperature / Temperatura fluido	-20°C +90°C
Ambient temperature / Temperatura ambiente	-20°C +50°C



ORDERING CODE / CODICE ORDINAZIONE

18 C ** 00 3 1 ** **

Setting (example)	
15	R 1.5
20	R 2.0

Hole F Diameter (example)	
00	No hole.
01	F Ø 0.1

Ports size	
02	1/4 BSPP
03	3/8 BSPP
04	1/2 BSPP
05	3/4 BSPP
06	1" BSPP

Standard code	A thread	B thread	L	LB	LA	Hex	R Std	Weight (kg)	Max. Flow (l/m)	Max. Pressure (bar)
18C0900310202	1/4	1/4	50	14	19	19	0.9	0.09	25	350
18C1500310303	3/8	3/8	58	17	23	24	1.5	0.16	50	350
18C2300310404	1/2	1/2	62	18	22.5	27	2.3	0.20	80	350
18C2500310505	3/4	3/4	75	21	23.5	32	2.5	0.30	150	350
18C2800310606	1"	1"	85	23	25	41	2.8	0.55	180	350

* On request versions: Please, contact our customer service / Versioni su richiesta: Per cortesia contattare il ns. servizio clienti.